


Cuscinetti a sfera fila unica W6008-2RS1-SKF - W6008-2RS1-SKF

<https://www.123cuscinetti.ch/cuscinetti-supporti/cuscinetti-sfera/fila-unica/w6008-2rs1-skf>

Dimensions d'encombrement		Charges de base		Vitesses de base		Désignation
d	D	B	Dynamique C	statique C ₀	Vitesse de référence tr/min	Vitesse limite
40	68	15	14	10,8	-	6300
 <p>Technical drawing showing the bearing dimensions and coefficients. The drawing includes the outer diameter (D=68), inner diameter (d=40), and thickness (B=15). It also shows the dynamic load capacity (C=14), static load capacity (C₀=10.8), and the reference speed (6300 tr/min). The designation is W 6008-2RS1. Coefficients of safety are given as k_r 0,025 and k_t 15.</p>						

CARATTERISTICHE DEL PRODOTTO

Marchio	SKF
N° Ean13	7316570648621
Diametro interno	40 mm
Impermeabilizzazione	Tenuta su ambo i lati
Gabbia	Lamiera
Radial class	CN
Diametro esterno	68 mm
Spessore	15 mm
Velocità limite	6300 rpm
Peso	191 g
Carico dinamico	14.6 kN
Carico statico	11.4 kN
Imballaggio	1

contatto@123cuscinetti.ch

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE