


Ralle regispinta WS1730-IKO - WS1730-IKO

<https://www.123cuscinetti.ch/accessori/rondella/ralle-regispinta/ws1730-iko>

IKO
THRUST BEARINGS
Thrust Needle Roller Bearings



Shaft dia. mm	Identification number							
	Thrust needle roller bearing	Mass (Ref.) g	Thrust washer	Mass (Ref.) g	Inner ring	Outer ring	Mass (Ref.) g	
17	NTB 1730	4.5	AS 1730	3.7	WS 1730	GS 1730	10.2	

Boundary dimensions mm							Basic dynamic load rating C N	Basic static load rating C ₀ N	Allowable rotational speed ⁽²⁾ rpm	
d	D	D _w	s	B	r _s min ⁽¹⁾	C ₁				
17	30	2	1	2.75	0.3	20	28	9 320	32 900	11 000

Notes: (1) Minimum allowable value of chamfer dimension r
(2) Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 25% of this value is allowable.

CARATTERISTICHE DEL PRODOTTO

Marchio	IKO
N° Ean13	3663952298863
Diametro interno	17 mm
Diametro esterno	30 mm
Spessore	2.75 mm
Materiale	ACCIAIO
Peso	10 g
Imballaggio	1

contatto@123cuscinetti.ch

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE