


Ralle regispinta WS3552-IKO - WS3552-IKO

<https://www.123cuscinetti.ch/accessori/rondella/ralle-regispinta/ws3552-iko>

IKO
THRUST BEARINGS
Thrust Needle Roller Bearings



| Shaft dia. mm | Identification number | | | | | | | |
|---------------|------------------------------|---------------|----------------|---------------|------------|------------|---------------|--|
| | Thrust needle roller bearing | Mass (Ref.) g | Thrust washers | Mass (Ref.) g | Inner ring | Outer ring | Mass (Ref.) g | |
| 35 | NTB 3552 | 10.6 | AS 3552 | 8.9 | WS 3552 | GS 3552 | 31.5 | |

| Boundary dimensions mm | | | | | | | Basic dynamic load rating C N | Basic static load rating C ₀ N | Allowable rotational speed ⁽²⁾ rpm | |
|------------------------|----|---|---|--------------------|----------------|----------------|-------------------------------|---|---|-------|
| d | D | s | B | r _s max | C ₁ | C ₂ | | | | |
| 35 | 52 | 2 | 1 | 3.5 | 0.6 | 39 | 50 | 16 300 | 81 900 | 5 500 |

Notes: ⁽¹⁾ Minimum allowable value of chamfer dimension r
⁽²⁾ Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 25% of this value is allowable.

CARATTERISTICHE DEL PRODOTTO

| | |
|------------------|------------------|
| Marchio | IKO |
| N° Ean13 | 3663952299068 |
| Diametro interno | 35 mm |
| Diametro interno | 1.378" inch |
| Diametro esterno | 52 mm |
| Diametro esterno | 2.047" inch |
| Spessore | 3.5 mm |
| Spessore | 0.138" inch |
| Materiale | ACCIAIO |
| Peso | 31 g |
| Imballaggio | - |
| Standard | Nessuno standard |

contatto@123cuscinetti.ch

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE