


## Cuscinetti conico 2561X-2523-TIMKEN - 2561X-2523-TIMKEN

<https://www.123cuscinetti.ch/cuscinetti-supporti/cuscinetti-rulli/conico/2561x-2523-timken>

**TAPERED ROLLER BEARINGS**  
SINGLE-ROW • TYPE TS

**TYPE TS**



| Bearing Dimensions |        |         | Load Ratings                           |                         |  |                         |                        |       | Part Number |  |
|--------------------|--------|---------|--|-------------------------|--|-------------------------|------------------------|-------|-------------|--|
| Bore d             | O.D. D | Width T | Dynamic <sup>(1)</sup> C <sub>10</sub> | Factor <sup>(2)</sup> e | Dynamic <sup>(1)</sup> C <sub>90</sub> | Factor <sup>(3)</sup> K | Static C <sub>10</sub> | Inner | Outer       |  |
| mm                 | mm     | mm      | N                                      |                         | N                                      |                         | N                      |       |             |  |
| 30.213             | 69.850 | 23.812  | 82700                                  | 0.27                    | 21700                                  | 1.14                    | 94400                  | 2561X | 2523        |  |
| 1.1895             | 2.7500 | 0.9375  | 18500                                  |                         | 4800                                   | 2.08                    | 23200                  |       |             |  |

| Bearing Dimensions |         |                          |   |   |   |   |                                    |                               |                | Geometry Factors |                |     | Bearing Weight |      |
|--------------------|---------|--------------------------|---|---|---|---|------------------------------------|-------------------------------|----------------|------------------|----------------|-----|----------------|------|
| Width B            | Width C | ER. Dr. α <sup>(1)</sup> | Max Shaft Fillet Radius R <sub>f</sub> <sup>(2)</sup> | Backing Shoulder Dia. d <sub>s</sub> <sup>(3)</sup> | Max Housing Fillet Radius r <sub>h</sub> <sup>(4)</sup> | Backing Shoulder Dia. D <sub>s</sub> <sup>(5)</sup> | Cage A <sub>1</sub> <sup>(6)</sup> | A <sub>2</sub> <sup>(7)</sup> | G <sub>1</sub> | G <sub>2</sub>   | C <sub>3</sub> |     |                |      |
| mm                 | mm      | mm                       | mm  | mm  | mm  | mm  | mm                                 | mm                            |                |                  |                | kg  |                |      |
| 24.714             | 19.950  | -8.8                     | 2.3   | 36.5  | 40.8  | 1.3   | 64.0                               | 61.8                          | 8.8            | 1.5              | 25.0           | 5.8 | 0.9058         | 0.46 |
| 0.9730             | 0.7900  | -0.34                    | 0.09  | 1.44  | 1.57  | 0.05  | 2.52                               | 2.40                          | 0.05           | 0.06             |                |     | 1.02           |      |

### CARATTERISTICHE DEL PRODOTTO

|                  |               |
|------------------|---------------|
| Marchio          | TIMKEN        |
| N° Ean13         | 3663952309903 |
| Diametro interno | 30.21 mm      |
| Diametro esterno | 69.85 mm      |
| Spessore         | 23.81 mm      |
| Imballaggio      | 1             |

[contatto@123cuscinetti.ch](mailto:contatto@123cuscinetti.ch)

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE